INDUSTRIAL RANGE RED METAL PRIMER



DESCRIPTION

Africa Paints Red Metal Primer is an excellent water-based primer for steel & galvanised iron surfaces.

USES

Suitable for Mild Steel, Perlins Tubalar, Section & Fabrication

BENEFITS

- Excellent Adhesion
- Good Hiding Power
- Apply with Brush or Roller
- Interior & Exterior Use
- Quality Guaranteed

APPLICATION

Stir the contents thoroughly before use. This product can be thinned down for spray application. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush, paint roller or airless spray. Clean tools (brushes & rollers) with Water immediately after use

SPREADING RATE

This product will cover approximately 7-9m²/litre, (when thinned down)

SURFACE PREPARATION

NEW SURFACES: Surface/s must be thoroughly clean, dry & in sound condition before commencing work

IRON & STEEL: Clean & remove all oil/grease prior to using this product. Apply one coat of Africa Paints Red Metal Primer, followed by two topcoats of paint in the desired finish.

GALVANISED IRON: Clean & remove all oil/grease prior to applying one coat of Africa Paints Galvinised Iron Primer. Apply two topcoats of paint in the desired finish

TECHNICAL DATA		
TYPE	Acrylic	
FINISH	Matt	
DRYING TIME @ 25°C	Touch Dry: 30 Minutes	
RE-COATING TIME	4 Hours	
VISCOSITY	95 - 108 Kµ	
WASH ABILITY		
PACK SIZE	5Lt / 20Lt	

PRECAUTIONS: Do not apply if rain is imminent ◆ Apply at an ambient temperature lower than 35°C
• Keep out of reach of children ◆ Wash hands with Mineral Turpentine immediately after use ◆ Skin or Eye contact: clean with fresh water and consult a physician if necessary ◆ Wear protective clothing such as Overall, Gloves, Goggles etc

QUALITY GUARANTEE: This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

PRODUCT DATA SHEET

