# INDUSTRIAL RANGE

ROAD MARKING



# DESCRIPTION

Africa Paints Road Marking Paint is a quick drying alkyd-based paint suitable for new & previously painted tar, concrete roads & parking lot surfaces. It is a durable product with excellent adhesion.

# USES

- Tar & Concrete Road surfaces
- Sign writing of Roads
- Marking of Parking areas

# **BENEFITS**

- Quick-drying
- Good Durability
- Excellent Hiding Power
- Apply with Brush, Roller or Spray
- Interior & Exterior Use
- Quality Guaranteed

#### **APPLICATION**

Stir the contents thoroughly before use For colour consistency, ensure that batch numbers are the same on all cans. For spray application thin down by up to 10% with Africa Paints Road Marking Paint Reducer. Apply one coat with a paintbrush, paint roller or airless spray & allow 15 minutes to dry. Clean tools (brushes, rollers & spraying equipment) with Africa Paints Road Marking Paint Reducer (thinners) immediately after use

# **COLOUR RANGE**

Available in 3 standard colours: White, Yellow & Red

#### SPREADING RATE

This product will cover approximately 5m²/litre, (new roads) & 8m/litre (previously painted roads) depending on surface porosity.

# SURFACE PREPARATION

**NEW & PREVIOUSLY PAINTED SURFACES:** Surface/s must be thoroughly clean (free from gravel), dry & in sound condition before commencing work

Apply one coat of Africa Paints Road Marking Paint direct to the surface by laying-on an even coat of paint

TECHNICAL DATA	
TYPE	Solvent/Styrenated Alkyd
FINISH	Finish Matt
DRYING TIME @ 25°C	Touch Dry: 1 - 3Minutes
RE-COATING TIME	15 Minutes
WASH ABILITY	
STORAGE	Dry & Cool area
PACK SIZE	1Lt / 5Lt

PRECAUTIONS: Do not apply if rain is imminent ● Apply at an ambient temperature lower than 35°C
• Keep out of reach of children ● Wash hands with Mineral Turpentine immediately after use ● Skin or Eye contact: clean with fresh water and consult a physician if necessary ● Wear protective clothing such as Overall, Gloves, Goggles etc

**QUALITY GUARANTEE:** This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

# PRODUCT DATA SHEET

